


等辺アングル 一般鋼材用延鋼材 SS JIS G3101(1987)



サイズ		質量 kg/m		5.5	6.0	7.0	7.0	8.0	9.0	12.0
A × B	厚さ									
20 × 20	3	0.885	■□	4.87						
25 × 25	3	1.12	■□	6.16						
30 × 30	3	1.36	■□	7.48						
	5	2.16	■□	11.9						
40 × 40	3	1.83	■□	10.1	11.0					
	5	2.95	■□	16.2	17.7					
45 × 45	4	2.74		15.1	16.4					32.9
50 × 50	4	3.06	■□	16.8	■ 18.4	21.4	24.5	27.5	33.7	36.7
	5	3.77			22.6					
	6	4.43	■□	24.4	■ 26.6	31.0	35.4	39.9	48.7	53.2
	8	5.78		31.8	35.0					69.4
60 × 60	4	3.68			22.1					44.2
	5	4.55		25.0	27.3					54.6
	6	5.41			32.5					
65 × 65	6	5.91	■□	32.5	■ 35.5	41.4	47.3	53.2	65.0	70.9
	8	7.66		42.1	46.0	53.6	61.3	68.9	84.3	91.9
70 × 70	6	6.38			38.3					
75 × 75	6	6.85	■□	37.7	■ 41.1	48.0	54.8	61.6	75.4	82.2
	9	9.96	■□	54.8	59.8	69.7	79.7	89.6	110	120
	12	13.0		71.5	78.0					
80 × 80	6	7.32			43.9					
90 × 90	6	8.28			49.5					99.4
	7	9.59		52.7	57.5	67.1	76.7	86.3	105	115
	10	13.3		73.2	79.8	93.1	106	120	146	160
	13	17.0		93.5	102	119	136	153	187	204
100 × 100	7	10.7		58.8	64.2	74.9	85.6	96.3	118	128
	10	14.9		82.0	89.4	104	119	134	164	179
	13	19.1		105	115	134	153	172	210	229
120 × 120	8	14.7			88.2					
130 × 130	9	17.9		98.4	107	125	143	161	197	215
	12	23.4		129	140	164	187	211	257	281
	15	28.8		158	173	202	230	259	317	346
150 × 150	10	22.9			137.4					
	12	27.3		150	164	191	218	246	300	328
	15	33.6		185	202	235	269	302	370	403
	19	41.9		230	251	293	335	377	461	503
200 × 200	15	45.3		249	272	317	362	408	498	544
	20	59.7		328	358	418	478	537	657	716
	25	73.6		405	442	515	589	662	810	883
250 × 250	25	93.7			562.2					
	35	128.0			768					

不等辺アングル 一般構造用圧延鋼材 SS JIS G3101(1987)

サイズ		質量 kg/m	5.5	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A × B	厚さ									
50 × 75	6	5.67	31.2	34.0	39.7	45.4	51.0	56.7	62.4	68.0
75 × 90	6	7.56	41.6	45.4	52.9	60.5	68.0	75.6	83.2	90.7
	9	11.0	60.5	66.0	77.0	88.0	99.0	110	121	132
75 × 100	7	9.32	51.3	55.9	65.2	74.6	83.9	93.2	103	112
	10	13.0	71.5	78.0	91.0	104	117	130	143	156
	13	16.5	90.8	99.0	116	132	148	165	182	198
75 × 125	7	10.7	58.8	64.2	74.9	85.6	96.3	107	118	128
	10	14.9	82.0	89.4	104	119	134	149	164	179
	13	19.1	105	115	134	153	172	191	210	229
90 × 125	9	14.6	80.3	87.6	102.2	116.8	131.4	146	160.6	175.2
	10	16.1	88.6	96.6	113	129	145	161	177	193
	13	20.6	113	124	144	165	185	206	227	247
90 × 150	9	16.4	90.2	98.4	115	131	148	164	180	197
	12	21.5	118	129	150	172	194	215	236	258
100 × 150	9	17.1	94.0	103	120	137	154	171	188	205
	12	22.4	123	134	157	179	202	224	246	269
	15	27.7	152	166	194	222	249	277	305	332

不等辺不等厚アングル 一般構造用圧延鋼材 SS JIS G3101(1987)


サイズ					質量 kg/m	5.5	6.0	7.0	8.0	9.0	11.0	12.0
A × B	t <sub>1</sub>	t <sub>2</sub>	r <sub>1</sub>	r <sub>2</sub>								
200 × 90	9	14	14	7	23.3	128	140	163	186	210	256	280
250 × 90	10	15	17	8.5	29.4	162	176	206	235	265	323	353
	12	16	17	8.5	33.7	185	202	236	270	303	371	404
300 × 90	11	16	19	9.5	36.3	200	218	254	290	327	399	436
	13	17	19	9.5	41.3	227	248	289	330	372	454	496
350 × 100	12	17	22	11	45.3	249	272	317	362	408	498	544
400 × 100	13	18	24	12	53.8	296	323	377	430	484	592	646

■ラー・グレー □白

チャンネル 一般構造用圧延鋼材 SS JIS G3101(1987)

サイズ			質量 kg/m	5.5	6.0	7.0	8.0	9.0	10.0	11.0	12.0	
A × B	t <sub>1</sub>	t <sub>2</sub>										
40 × 75	5	7	6.92	■□	38.1	41.5	48.4	55.4	62.3	69.2	76.1	83.0
50 × 100	5	7.5	9.36	■□	51.5	56.2	65.5	74.9	84.2	93.6	103	112
65 × 125	6	8	13.4	■□	73.7	80.4	93.8	107	121	134	147	161
75 × 150	6.5	10	18.6	■□	102	112	130	149	167	186	205	223
	9	12.5	24.0	□	132	144	168	192	216	240	264	288
75 × 180	7	10.5	21.4	□	118	128	150	171	193	214	235	257
80 × 200	7.5	11	24.6	□	135	148	172	197	221	246	271	295
90 × 200	8	13.5	30.3	□	167	182	212	242	273	303	333	364
90 × 250	9	13	34.6		190	208	242	277	311	346	381	415
	11	14.5	40.2		221	241	281	322	362	402	442	482
90 × 300	9	13	38.1		210	229	267	305	343	381	419	457
	10	15.5	43.8		241	263	307	350	394	438	482	526
	12	16	48.6		267	292	340	389	437	486	535	583
100 × 380	10.5	16	54.5		300	327	382	436	490	545	600	654
	13	20	67.3		370	404	471	538	606	673	740	808

H型鋼 建築鋼材用圧延材 JIS G3136(1994)




■細巾系列

サイズ				質量 kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0
A × B	t <sub>1</sub>	t <sub>2</sub>	r									
100 × 50	5	7	8	9.3	55.8	65.1	74.4	83.7	93.0	102	112	121
125 × 60	6	8	9	13.1	78.6	91.7	105	118	131	144	157	170
150 × 75	5	7	8	14.0	84.0	98.0	112	126	140	154	168	182
175 × 90	5	8	8	18.0	108	126	144	162	180	198	216	234
200 × 100	5.5	8	8	20.9	125	146	167	188	209	230	251	272
248 × 124	5	8	8	25.1	151	176	201	226	251	276	301	326
250 × 125	6	9	8	29.0	174	203	232	261	290	319	348	377
298 × 149	5.5	8	13	32.0	192	224	256	288	320	352	384	416
300 × 150	6.5	9	13	36.7	220	257	294	330	367	404	440	477
346 × 174	6	9	13	41.2	247	288	330	371	412	453	494	536
350 × 175	7	11	13	49.4	296	346	395	445	494	543	593	642
396 × 199	7	11	13	56.1	337	393	449	505	561	617	673	729
400 × 200	8	13	13	65.4	392	458	523	589	654	719	785	850
446 × 199	8	12	13	65.1	391	456	521	586	651	716	781	846
450 × 200	9	14	13	74.9	449	524	599	674	749	824	899	974
496 × 199	9	14	13	77.9	467	545	623	701	779	857	935	1,013
500 × 200	10	16	13	88.2	529	617	706	794	882	970	1,058	1,147
600 × 200	11	17	13	103	618	721	824	927	1,030	1,133	1,236	1,339

※ SN 規格もあります。

H型鋼 建築鋼材用圧延材 JIS G3136(1994)



■広巾系列

サイズ				質量 kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0
A × B	t <sub>1</sub>	t <sub>2</sub>	r									
100 × 100	6	8	8	16.9	101	118	135	152	169	186	203	220
125 × 125	6.5	9	8	23.6	142	165	189	212	236	260	283	307
150 × 150	7	10	8	31.1	187	218	249	280	311	342	373	404
175 × 175	7.5	11	13	40.4	242	283	323	346	404	444	485	525
200 × 200	8	12	13	49.9	299	349	399	449	499	549	599	649
250 × 250	8	13	13	65.9	395	461	527	593	659	725	791	857
	11	11	13	63.8	383	447	510	574	638	702	766	829
	9.	14	13	71.8	431	503	574	646	718	790	862	933
	14	14	13	81.6	490	571	653	734	816	898	979	1,061
300 × 300	9.	14	13	86.0	516	602	688	774	860	946	1,032	1,118
	12	12	13	83.4	500	584	667	751	834	917	1,001	1,084
	10	15	13	93.0	558	651	744	837	930	1,023	1,116	1,209
	15	15	13	105	630	735	840	945	1,050	1,155	1,260	1,365
	11	17	13	105	630	735	840	945	1,050	1,155	1,260	1,365
350 × 350	12	19	13	135	810	945	1,080	1,215	1,350	1,485	1,620	1,755
400 × 400	13	21	22	172	1,032	1,204	1,376	1,548	1,720	1,892	2,064	2,236


※ SN 規格もあります。

■中巾系列

サイズ				質量 kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A × B	t <sub>1</sub>	t <sub>2</sub>	r								
148 × 100	6.	9	8	20.7	124	145	166	186	207	228	248
194 × 150	6.	9	8	29.9	179	209	239	269	299	329	359
244 × 175	7	11	13	43.6	262	305	349	392	436	480	523
294 × 200	8.	12	13	55.8	335	391	446	502	558	614	670
340 × 250	9.	14	13	78.1	469	547	625	703	781	859	937
390 × 300	10	16	13	105	630	735	840	945	1,050	1,155	1,260
440 × 300	11	18	13	121	726	847	968	1,089	1,210	1,331	1,452
488 × 300	11	18	13	125	750	875	1,000	1,125	1,250	1,375	1,500
588 × 300	12	20	13	147	882	1,029	1,176	1,323	1,470	1,617	1,764
700 × 300	13	24	18	182	1,092	1,274	1,456	1,638	1,820	2,002	2,184
800 × 300	14	26	18	207	1,242	1,449	1,656	1,863	2,070	2,277	2,484
900 × 300	16	28	18	240	1,440	1,680	1,920	2,160	2,400	2,640	2,880

※ SN 規格もあります。

軽量H型鋼 一般建築構造用溶接軽量H型鋼SWH400 JIS G3353(1990)



サイズ			質量 kg/m	定尺 (m) 重量					
A × B	t <sub>1</sub>	t <sub>2</sub>		7.0	8.0	9.0	10.0	11.0	12.0
150 × 75	3.2	4.5	8.84	61.9	70.7	79.6	88.4	97.2	106
150 × 100	3.2	4.5	10.6	74.2	84.8	95.4	106	117	127
175 × 90	3.2	4.5	10.5	73.5	84.0	94.5	105	116	126
200 × 100	3.2	4.5	11.9	83.3	95.2	107	119	131	143
	3.2	6.0	14.1	98.7	113	127	141	155	169
200 × 125	3.2	6.0	16.5	116	132	148	165	182	198
200 × 150	3.2	4.5	15.4	108	123	139	154	169	185
	3.2	6.0	18.9	132	151	170	189	208	227
250 × 125	3.2	4.5	14.9	104	119	134	149	164	179
	4.5	6.0	20.2	141	162	182	202	222	242
	4.5	9.0	25.9	181	207	233	259	285	311
250 × 150	3.2	4.5	16.6	116	133	149	166	183	199
	4.5	6.0	22.5	158	180	202	225	248	270
	4.5	9.0	29.4	206	235	265	294	323	353
300 × 150	3.2	4.5	17.9	125	143	161	179	197	215
	4.5	6.0	24.3	170	194	219	243	267	292
	4.5	9.0	31.2	218	250	281	312	343	374
300 × 175	4.5	6.0	26.7	187	214	240	267	294	320
	4.5	9.0	34.7	243	278	312	347	382	416
350 × 175	4.5	6.0	28.4	199	227	256	284	312	341
	4.5	9.0	36.5	256	292	328	365	402	438
400 × 200	4.5	6.0	32.5	228	260	292	325	358	390
	4.5	9.0	41.8	293	334	376	418	460	502
	6.0	9.0	46.3	324	370	417	463	509	556
	6.0	12.0	55.4	388	443	499	554	609	665
450 × 200	4.5	9.0	43.5	304	348	392	435	478	522
	6.0	12.0	57.7	404	462	519	577	635	692

アイビーム 一般構造用圧延鋼材 SS400 JIS G3101(1987)

サイズ			1.0	5.5	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A × B	t <sub>1</sub>	t <sub>2</sub>									
100 × 75	5	8	12.9	71.0	77.4	90.3	103	116	129	142	155
125 × 75	5.5	9.5	16.1	88.6	96.6	113	129	145	161	177	193
150 × 75	5.5	9.5	17.1	94.0	103	120	137	154	171	188	205
150 × 125	8.5	14	36.2	199	217	253	290	326	362	398	434
180 × 100	6	10	23.6	130	142	165	189	212	236	260	283
200 × 100	7	10	26.0	143	156	182	208	234	260	286	312
200 × 150	9.	16	50.4	277	302	353	403	454	504	554	605
250 × 125	7.5	11.5	38.3	211	230	268	306	345	383	421	460
	10	19	55.5	305	333	388	444	500	555	610	666
300 × 150	8	13	48.3	266	290	338	386	435	483	531	580
	10	18.5	65.5	360	393	458	524	590	655	720	786
	11.5	22	76.8	422	461	538	614	691	768	845	922
350 × 150	9.	15	58.5	322	351	410	468	526	585	644	702
	12	24	87.2	480	523	610	698	785	872	959	1,046
400 × 150	10	18	72.0	396	432	504	576	648	720	792	864
	12.5	25	95.8	527	575	671	766	862	958	1,054	1,150
450 × 175	11	20	91.7	504	550	642	734	825	917	1,009	1,100
	13	26	115	632	690	805	920	1,035	1,150	1,265	1,380
600 × 190	13	25	133	732	798	931	1,064	1,197	1,330	1,463	1,596
	16	35	176	968	1,056	1,232	1,408	1,584	1,760	1,936	2,112